



# Filter Housing Standard

10" Standard



## Features

- 100% virgin materials - polypropylene or acrylonitrile styrene (AS)
- O-ring: Buna-N
- No chemicals added, ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Single recess top mounted O-ring design prevents pinching and leaks
- Built-in pressure relief / air bleed button (optional)
- Various cap design and connection size options
- Compatible with multiple filter cartridge types

Does your water source suffer from contaminants, sediment, or odors? GWS filter housings are the first step in solving your drinking water needs. Built with the highest quality virgin materials and reinforced to withstand the highest pressures, our filter housings can be used with a wide assortment of cartridges and media for applications in homes, restaurants, industry, and anywhere clean drinking water is a must.



Internal cap view



Multiple mounting bolt configurations



Recess mounted top O-ring design



Flat cap design (1/4" & 3/8" connection cap)



Round cap with optional relief valve (1/2" & 3/4" connection cap only)



Round cap design (1/4" & 3/8" connection cap)

## Models

Model Number	Connection	PRV	Cap Design	Cap Color	Sump Color	Box qty
<b>10" Standard Housings - 9 7/8"</b>						
<b>Standard Design</b>						
H06-2C-WW-RC	1/4" Compatible	No	Round Cap	White	White	12
H06-2C-WC-RC	1/4" Compatible	No	Round Cap	White	Clear	12
H06-2C-WW-FC	1/4" Compatible	No	Flat Cap	White	White	12
H06-2C-WC-FC	1/4" Compatible	No	Flat Cap	White	Clear	12
H06-3C-WW-FC	3/8" Compatible	No	Flat Cap	White	White	12
H06-3C-WC-FC	3/8" Compatible	No	Flat Cap	White	Clear	12
<b>BSP</b>						
H06-4B-WW-RC	1/2" BSP	No	Round Cap	White	White	12
H06-4B-WC-RC	1/2" BSP	No	Round Cap	White	Clear	12
H06V-4B-WW-RC	1/2" BSP	Yes	Round Cap	White	White	12
H06V-4B-WC-RC	1/2" BSP	Yes	Round Cap	White	Clear	12
H06-6B-WW-RC	3/4" BSP	No	Round Cap	White	White	12
H06-6B-WC-RC	3/4" BSP	No	Round Cap	White	Clear	12
H06V-6B-WW-RC	3/4" BSP	Yes	Round Cap	White	White	12
H06V-6B-WC-RC	3/4" BSP	Yes	Round Cap	White	Clear	12
<b>NPT</b>						
H06-4N-WW-RC	1/2" NPT	No	Round Cap	White	White	12
H06-4N-WC-RC	1/2" NPT	No	Round Cap	White	Clear	12
H06V-4N-WW-RC	1/2" NPT	Yes	Round Cap	White	White	12
H06V-4N-WC-RC	1/2" NPT	Yes	Round Cap	White	Clear	12
H06-6N-WW-RC	3/4" NPT	No	Round Cap	White	White	12
H06-6N-WC-RC	3/4" NPT	No	Round Cap	White	Clear	12
H06V-6N-WW-RC	3/4" NPT	Yes	Round Cap	White	White	12
H06V-6N-WC-RC	3/4" NPT	Yes	Round Cap	White	Clear	12

## Specifications

Product Series Name	Filter Housing - 10" Standard
Min. / Max. Operating Temperature	4.4°C - 40°C / 40°F - 104°F
Max. Operating Pressure	Polypropylene: 8.6 bar   125 psi AS (clear): 6.9 bar   100 psi

NSF certification listing not applicable for AS (clear) housings



# Filter Housing Standard

10" Standard

## Models

Model Number	Connection	PRV	Cap Design	Cap Color	Sump Color	Box qty
<b>10" Standard Housings - 9 3/4"</b>						
<b>Standard Design</b>						
H05-2C-WW-FC	1/4" Compatible	No	Flat Cap	White	White	12
H05-2C-WC-FC	1/4" Compatible	No	Flat Cap	White	Clear	12
<b>BSP</b>						
H05-4B-WW-FC	1/2" BSP	No	Flat Cap	White	White	12
H05-4B-WC-FC	1/2" BSP	No	Flat Cap	White	Clear	12
H05V-4B-WW-RC	1/2" BSP	Yes	Round Cap	White	White	12
H05V-4B-WC-RC	1/2" BSP	Yes	Round Cap	White	Clear	12
H05-6B-WW-RC	3/4" BSP	No	Round Cap	White	White	12
H05-6B-WC-RC	3/4" BSP	No	Round Cap	White	Clear	12
H05V-6B-WW-RC	3/4" BSP	Yes	Round Cap	White	White	12
H05V-6B-WC-RC	3/4" BSP	Yes	Round Cap	White	Clear	12
<b>NPT</b>						
H05-4N-WW-FC	1/2" NPT	No	Flat Cap	White	White	12
H05-4N-WC-FC	1/2" NPT	No	Flat Cap	White	Clear	12
H05V-4N-WW-RC	1/2" NPT	Yes	Round Cap	White	White	12
H05V-4N-WC-RC	1/2" NPT	Yes	Round Cap	White	Clear	12
H05-6N-WW-RC	3/4" NPT	No	Round Cap	White	White	12
H05-6N-WC-RC	3/4" NPT	No	Round Cap	White	Clear	12
H05V-6N-WW-RC	3/4" NPT	Yes	Round Cap	White	White	12
H05V-6N-WC-RC	3/4" NPT	Yes	Round Cap	White	Clear	12

## Specifications

Product Series Name	Filter Housing - 10" Standard
Min. / Max. Operating Temperature	4.4°C - 40°C / 40°F - 104°F
Max. Operating Pressure	Polypropylene: 8.6 bar   125 psi AS (clear): 6.9 bar   100 psi

NSF certification listing not applicable for AS (clear) housings



# Filter Housing Standard

20" Standard



## Features

- 100% virgin materials – polypropylene or acrylonitrile styrene (AS)
- O-ring: Buna-N
- No chemicals added ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Single recess top mounted O-ring design prevents O-ring pinching and leaks
- Built-in pressure relief / air bleed button (optional)
- Equipped with filter cartridge centering plug to ensure zero bypass



Does your water source suffer from contaminants, sediment, or odors? GWS filter housings are the first step in solving your drinking water needs. Built with the highest quality virgin materials and reinforced to withstand the highest pressures, our filter housings can be used with a wide assortment of cartridges and media for applications in homes, restaurants, industry, and anywhere clean drinking water is a must.



Housing cap with Pressure Relief Valve (PRV)



Housing cap mounting bolt hole design



PRV protection plate for protection during shipping



Single recess top mounted O-ring



Removable filter cartridge centering plug

Where **Water Gets Better**

## Models

Model Number	Connection	PRV	Cap Color	Sump Color	Box qty
<b>20" Standard Housings</b>					
<b>Standard Design</b>					
H09-3C-KB	3/8" Compatible	No	Black	Blue	6
H09-3C-KC	3/8" Compatible	No	Black	Clear	6
<b>BSP</b>					
H09-4B-KB	1/2" BSP	No	Black	Blue	6
H09-4B-KC	1/2" BSP	No	Black	Clear	6
H09V-6B-KB	3/4" BSP	Yes	Black	Blue	6
H09V-6B-KC	3/4" BSP	Yes	Black	Clear	6
<b>NPT</b>					
H09-4N-KB	1/2" NPT	No	Black	Blue	6
H09-4N-KC	1/2" NPT	No	Black	Clear	6
H09V-6N-KB	3/4" NPT	Yes	Black	Blue	6
H09V-6N-KC	3/4" NPT	Yes	Black	Clear	6

## Specifications

Product Series Name	Filter Housing - 20" Standard
Min. / Max. Operating Temperature	4.4°C - 40°C / 40°F - 104°F
Max. Operating Pressure	Polypropylene: 8.6 bar   125 psi AS (clear): 6.9 bar   100 psi
Connection	3/8", 1/2", and 3/4"

NSF certification listing not applicable for AS (clear) housings