



AQUAWAVE CLASSIC 75GPD



Purified Water Right at Your Tap

Aquawave Classic 75 GPD reverse osmosis drinking water system

100% virgin, sterile, and hygienic NSF Approved materials

Filter housings minimum burst pressure exceeds 400 psi / 27.5 bar

Patented lip seal design on housing prevents leaks and water hammer attack

Booster pump equipped with all aluminum end caps- provides better thermal management & service life

Chrome-plated plastic faucet

Optional PA.E / TankPAC RO storage tank

CE Certified booster pump and power adapter

Purefer™ series pre- and post-filters

Specifications

75GPD

Dimensions	14.6 x 10.6 x 18.5 inch 37 x 27 x 47 cm
Weight	21 lb 9.5 kg
Tube Size	1/4"
Operation Pressure	20 psi - 60 psi 1.4 bar - 4 bar
Maximum Pump Press	00 psi 6.9 bar
Power Input	110V or 220V 230 VAC
Power Consumption	24V 1.2 A 28W
Recommended Water Temperature	41°F - 100°F 5°C - 38°C
Maximum TDS	1000 ppm
Maximum Hardness	17 grain/gallon
Maximum Chlorine	0.2 ppm - 1.0 ppm Chlorine
Maximum Iron	0.3 mg/L
Maximum Manganese	0.05 mg/L
Maximum Turbidity	2 NTU
pH	6.0 - 8.5

Purefer™ Inside

The Aquawave Classic 75 GPD reverse osmosis drinking water system comes with following Purefer™ filters:

STAGE 1



PP1005

5 Micron
Polypropylene
(PP) Filter

- Removes Sediment, dirt, rust, pipe, scale, etc.,
- 100% Virgin PP

STAGE 2



M01-GT-BW

UDF Cartridge

- 100% pure coconut activated carbon
- Iodine number of 1000
- Carbon Block Filter

STAGE 3



M11-GT-WN

2-IN-1 BLOCKFREE
SERIES

- 100% pure coconut activated carbon
- Iodine number of 1000
- Carbon Block Filter

STAGE 4



75G-NSFREP-ROMEMBRANE

RO Membrane

- 75 GPD
- Thin Film Composite

STAGE 5



K02-GT-WW-TP

Granular Activated Carbon

- 100% pure coconut activated carbon
- Improved chlorine removal efficiency
- Bacteria-resistant

Have questions or need assistance? Contact us today